



Single Channel Audio Surveillance Kit

Description

Single Zone audio surveillance system designed to connect directly to our DVRs.

Kit Includes

- RM1 Pre-amplified microphone
- RM2 single channel interface adapter
- 12V DC adapter
- 3' RCA patch cable
- Warning label

Wiring Requirements

- stranded 22 gauge, 2 conductor, shielded cable. Distances up to 1500'

Caution

It is the responsibility of the installation company and end user to comply with state and federal privacy laws regarding the use of audio surveillance equipment. If you are unfamiliar with these laws, consult a qualified attorney. In most cases, posting the provided warning labels in plain view is all that is required.

Warranty

1 year parts and labor.

Made in U.S.A.



RM1 Microphone Specifications

- Omni-directional Electret element. 25' range in all directions
- Low noise MOSFET pre-amplifier.
- Line level unbalanced output.
- Adjustable gain.
- Treble boost circuit. Selectable on/off. Enhances clarity of time lapse recordings.
- Limiter circuit selectable on/off.
- Easy cable run termination.
- Flush or surface mountable. Can be mounted on a single gang electrical box.
- Power: 12V DC @ 10mA.

RM2 Interface Adapter Specifications

- Standard RCA jack for connection to our DVRs
- Easy cable run termination.
- LED power indicator
- Power: 12V DC @ 10mA.
- Reverse polarity protected and fused
- Dimensions W 1.75" X L 2.75" X H 1.25"



Dealer Info:



Visit Us Online
www.rugged-cctv.com

Toll-Free
866.301.2288