

5327 Cedar Creek Drive Kemp, Texas 75143 Toll Free: 866-301-CCTV

Phone: 903-498-3240 Fax: 903-498-8989

website: www.rugged-cctv.com email: sales@rugged-cctv.com

Description

Powers up to 8 RM1 series microphones and distributes their audio outputs to individual RCA (or optional 3.5mm) jacks. Designed for connecting Rugged microphones to equipment with un-balanced, line level inputs.

Includes

- RMI8 Interface adapter
- 12 V DC AC adapter
- Eight 3' RCA or Eight 3' 3.5mm patch cables.

Options

Specify: RCA output connectors or 3.5mm.

Wiring Requirements

• Stranded 22-gauge, 2-conductor shielded cable. Distances up to 1500'.

RMI8 8 Channel Interface Apapter



RMI8 Interface Adapter Specifications

- Standard RCA or 3.5mm jacks for connection to tape recorders, etc.
- Easy cable run terminations
- LED power indicator
- Power: 12V DC @ 40mA
- Reverse polarity protected and fused
- Dimensions: W 2.75 x L 4.38 x H 1.56

Caution

It is the responsibility of the installation company and end user to comply with state and federal privacy laws regarding the use of audio surveillance equipment. If you are unfamiliar with these laws, consult a qualified attorney. In most cases, posting the provided warning labels in plain view is all that is required.

Warranty

1 year parts and labor.